

Classica

Tuft gauge	1/10 loop pile		ISO 2424
Pilecomposition	100% PA SDN		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	AB, Silent Backing		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 986
Pile Weight	550 gr/m ²		ISO 8543
Total weight	1650/2100 gr/m ²	± 15%	ISO 8543
Pile height	3.5 mm		ISO 1765
Total Height	5.5/6.5 mm		ISO 1765
Number of knots	181.240/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1		EN 13501-1
Use Area	Heavy project use (33)		EN 1307
GUT Nr.	477CC0CE GUT		www.pro-dis.info
Sound Insulation	Ca. 23/29 dB		ISO 10140
Thermal resistance	0,062 M ² KW		ISO 8302
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Electrostatic charging	<2 kV		ISO 6356
Luxury class	LC2		EN 1307
Pictures	www.condorcontract.com		

Floorsymbols



Certificates



www.blauer-engel.de/uz128

